



TEMPEST Level I All-in-One Multi-Domain Computer

Product Data

Model - DHT-109 (Level I)

Description

API's DHT-109 All-in-One Multi-Domain TEMPEST Level I computer offers top performance using Intel® Core™ 2 Duo CPU technology. The DHT-109 utilizes low power components that increase energy savings by more than half over standard desktop configurations. The low wattage components also allow the DHT-109 to operate without fans resulting in noise-free operation and maximized reliability.

Modular, scalable and transitional options permit either Thin Client or PC configurations. The sleek All-in-One design features an integrated 22" widescreen display. The DHT-109's space saving features are offered at their best resulting in a non-clutter, operational environment.

The DHT-109 can be ordered with an embedded red-black KVM switch allowing a single TEMPEST display, keyboard and mouse to access both high and low-side networks. This is achieved by the secure TEMPEST Level I computer contained within and a low-side computer connected externally via the isolated KVM port.

The combined features greatly improve security configuration control and eliminate the security risks associated with interconnected equipment from different suppliers at a system level.

Features

- Certified to NSTISSAM TEMPEST/1-92 Level I and NATO SDIP-27 A standard (formerly AMSS 720B)
- Equipped with Intel® Core 2 Duo Processor
- Up to 4GB DDR2 Synch Dram
- An integrated 22" widescreen TFT active matrix LCD provides high resolution and excellent contrast ratio
- Intel® GME965 Express chipset with Intel Graphics
- Media Accelerator X3100, providing sharper images and higher performance on the demanding applications of today and tomorrow
- Configuration options that include lockable/removable solid-state hard drives for high reliability.
- Hassle free quick-connect interface connectors
- Fiber100BaseFX or 1000BaseSX
- Available in a Thin Client diskless configuration
- DataKey security options
- Microsoft® Windows® XP/Vista Compliant
- Industry leading three-year warranty





TEMPEST Level I All-in-One Multi-Domain Computer

Specifications

Model - DHT-109 (Level I)

Processor

Intel Core 2 Duo, 2.2GHz T7500, 4MB L2 Cache, 800MHz FSB

Chipset

Intel® GME965 chipset

Memory

1GB DDR2 Synch Dram PC2-5300 (667-MHz) Non ECC (1 x 1GB) standard.
Two
DDR2 sockets supporting up to 4GB DDR2 SDRAM

Graphics

Integrated VGA Intel® GME965 integrated graphics (GMAX3100)

Display

LCD Size: 22"
Aspect Ratio: 16:10
Minimum Contrast Ratio: 1000:1
Native Resolution: 1680 x 1050
Height adjustable stand

Available I/O Ports

Power plug
Datakey Token Receptacle
Serial, 1 standard 9 pin D-sub interface
USB, 4 quick connect tool-less mini-connector
TEMPEST Mouse, 3 ft. cable, tool-less connector
TEMPEST Keyboard, 3 ft cable tool-less connector
KVM switch option: External Video, Keyboard and Mouse
1 Parallel Port

Power

Autosensing power supply
Frequency: 50-60 Hz
Max. Power: 150 Watt

Operating System

Windows XP Professional SP2, Windows Vista Business 32, Windows Vista Business 64, XP embedded

Available Options

Media Devices
CD-RW/DVD-ROM Combo Drive

Hard Drives

Rotating Rugged Hard Drives

100-GB SATA 3.0-Gb/s Removable /Lockable Rugged Hard Drive (16MB Cache, 7200 RPM) - 350G operating shock, 1000G non-operating shock
Second 100-GB SATA 3.0-Gb/s Removable /Lockable Rugged Hard Drive 16MB Cache, 7200 RPM) - 350G operating shock, 1000G non-operating shock

Solid State Rugged Hard Drives

32GB SATA 1.5-Gb/s Removable/Lockable Solid State Rugged Hard Drive
Second 32GB SATA 1.5-Gb/s Removable/Lockable Solid State Rugged Hard Drive
64GB SATA 1.5-Gb/s Removable/Lockable Solid State Rugged Hard Drive
Second 64GB SATA 1.5-Gb/s Removable/Lockable Solid State Rugged Hard Drive

Removable Storage

Integrated receptacle w/ Datakey NFX Token

Network

Fiber 100BaseFX, 1000BaseSX

Physical Specifications

Height: 17.6" (44.7 cm)
Width: 20.4" (51.8 cm)
Depth: 10.7" (27.2 cm)
Weight w/Stand: 37 lbs (16.78 kg)

Operating Environment

Temperature
Operating: 50° to 95° F (10° to 35° C)
Non- Operating: -22° to 140° F (-30° to 60° C)

Humidity

Operating: 20% to 80%
Non- Operating: 10% to 90%

Altitude

Operating: 0 to 10,000 Ft (0-3,048m)
Storage: 0 to 30,000 Ft (0-9,144m)

Warranty

3-year on parts and labor

Advanced Programs, Inc. is an NSA-endorsed test services facility and an NSA-endorsed TEMPEST manufacturing facility.

Technical Specifications are subject to change without notice. U.S.A. export controls apply to these products.

E & OE - 11/19/09



HEADQUARTERS - UNITED STATES

Advanced Programs, Inc.
7125 Riverwood Drive
Columbia, MD 21046 U.S.A.
Phone: 410-312-5800 Fax 410-312-5850
<http://www.advprograms.com>

UNITED KINGDOM

API Europe Limited
Vanitec House, Cornbrash Park
Chippenham, Wiltshire, SN14 6RA, UK
Phone +44(0)1249 448777 Fax +44(0)1249 448765
<http://www.api-europe.com>